



AMETA
SOLUTION

Anti-Spatter Welding

70-04

PRODUCT TYPE

Protective spray for gas welding.
Special separation agent for plastic processing.
The **Anti-Spatter** spray prevents the adhesion of weld spatter on treated parts.
Prevents the fixation of spatter on gas welding nozzles and on nozzle for M.I.G. welding stations.

UTILISATION

Apply a thin and even layer of spray along the planned welding seam. Gas welding nozzles can be kept clean from contamination with frequent thin spray coatings.
Ensure equipment is shut-off before application.

ADVANTAGES AND PROPERTIES

- Free from fluorocarbons and silicone oils.
- Contains a foam indicator.
- 98% of active product.
- Neutral product, no reaction on the sprayed surface.
- Can be easily removed with warm water.
- Concentrated product non-diluted; economic at use.

German Union for Welding Technology
declared the 70-04 as the best product
Of its kind. 01/04/1999



RECOMMENDATIONS

Non flammable.
Follow label instructions.

PACKAGING

Description	Format	No. Produit
Spray	300 ml	70-04
Paste	250 gr	71-04
Liquid	960 ml	75-0401
Liquid	4 liters	75-0404
Liquid	10 liters	75-0410
Liquid	20 liters	75-0420
Liquid	205 liters	75-0445



70-04 / 75-04

Anti Spatter Spray

Colour	white
Thickness	1 g/cm ³



3556, boul. des Entreprises
Terrebonne (QC) Canada J6X 4J8
1-888-452-6382 – (450) 477-3102
F (450) 477-6664

ametasolution.com