

Meta-foam red





Description: The META-FOAM RED material is more rigid with faster cut and longer life compared to the black one or the blue one.


Main features and benefits: The META-FOAM RED offers a longer lifetime in heavy application.

Recommended applications: The META-FOAM RED is used for mechanically cleaning all types of welding, for rapidly removing scale and oxidation, for satin finishing small surfaces, for removing paints or other clogging materials such as salt, rust, grease, oil and protective waxes.


Work surfaces: Stainless steel, standard or alloyed steel, aluminum, titanium, nonferrous materials and alloys, fibre glass, plastic or plastic reinforced by fibre glass, stone or wood.



Size (Inches)	Max RPM	RPM optimal	N° Product	
Meta-foam red with fiberglass backing pad				
4 1/2 x 7/8	11,000	8,600	68-045R	10
5 x 7/8	9,800	7,800	68-050R	10
7 x 7/8	7,000	5,600	68-070R	10



Meta-foam red with hole				
4 x 1/2 x 1/4	8,000	6,000	68-004R	10
6 x 1/2 x 1/4	5,350	4,100	68-006R	10
8 x 1/2 x 1/4	4,000	2,800	68-007R	10



Meta-foam red with 1/4" shaft				
4 x 1/2 x 1/4	8,000	6,000	68-400R	10

**Adaptor shaft 1/4
for Meta-foam red with hole**

68-001A

To be use with only one
Meta-foam red

68-002A

To be use with one or more
Meta-foam red

